



Chain and Cable Lube

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)
Issue date: 9/11/2016 Revision date: 6/9/2022 Version: 2.0

SECTION 1: Identification

1.1. Product identifier

Product form : Mixture
Product name : Chain and Cable Lube
Product code : 16-CCL

1.2. Recommended use and restrictions on use

Recommended use : Multi-Purpose Lubricant

1.3. Supplier

Manufacturer

Blaster LLC
8500 Sweet Valley Drive
44125 Valley View, Ohio - USA
T (216) 901-5800 - F (216) 901-5801
www.blasterproducts.com

Distributor

Canadian Tire
2190 Yonge St.
6th Floor Toronto,
Ontario M6J 1R5 Canada
416-925-9592

1.4. Emergency telephone number

Emergency number : Chemtrec (800) 424-9300

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification (GHS CA)

| | | |
|--------------------|------|--|
| Flam. Aerosol 2 | H223 | Flammable aerosol |
| Press. Gas (Diss.) | H280 | Contains gas under pressure; may explode if heated |
| Asp. Tox. 1 | H304 | May be fatal if swallowed and enters airways |

2.2. GHS Label elements, including precautionary statements

This product is a consumer product and is labeled in accordance with the US Consumer Product Safety Commission regulations. The actual container label will not include the label elements below. The labeling below applies to industrial/professional products.

GHS CA labeling

Hazard pictograms (GHS CA)



Signal word (GHS CA)

: Danger

Hazard statements (GHS CA)

: H223 - Flammable aerosol
H280 - Contains gas under pressure; may explode if heated
H304 - May be fatal if swallowed and enters airways

Precautionary statements (GHS CA)

: P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 - Do not spray on an open flame or other ignition source.
P251 - Do not pierce or burn, even after use.
P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor.
P331 - Do NOT induce vomiting.
P405 - Store locked up.

Chain and Cable Lube

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

P410+P403 - Store in a well-ventilated place.

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS CA)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

| Name | Chemical name / Synonyms | Product identifier | % | Classification according to the Hazardous Products Regulation (February 11, 2015) |
|---|---|---------------------|---------|---|
| Distillates, petroleum, hydrotreated light naphthenic | Petroleum distillates, hydrotreated light naphthenic / Mineral oil, petroleum distillates, hydrotreated light naphthenic / Distillates (petroleum), hydrotreated light naphthenic / Distillates (petroleum) hydrotreated light naphthenic | CAS-No.: 64742-53-6 | 30 – 60 | Acute Tox. 4 (Inhalation:dust,mist);H332 Asp. Tox. 1;H304 |

Chain and Cable Lube

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

| Name | Chemical name / Synonyms | Product identifier | % | Classification according to the Hazardous Products Regulation (February 11, 2015) |
|---|--|---------------------|-----------|---|
| Petroleum distillates, hydrotreated light | Distillates (petroleum), hydrotreated light / Distillates, petroleum, hydrotreated light / Hydrotreated light distillate / Kerosene, hydrotreated / Petroleum distillates, hydrotreated light (A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C9-16 and boiling in the range of approximately 150-290°C.) / Odorless light petroleum hydrocarbons / Hydrocarbons, C11-14, n-alkanes, isoalkanes, cyclics, / Distillates (petroleum), hydro- treated light; Kerosine - unspecified [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C9 through C16 and boiling in the range of approximately 150°C to 290°C (302°F to 554°F).] / Light Aliphatic Hydrocarbon / c13-14 isoparaffin / Kerosene / Destillate (Erdöl), mit Wasserstoff behandelt leichte (C9-14 Aliphaten) | CAS-No.: 64742-47-8 | 30 – 60 | Flam. Liq. 3;H226 Asp. Tox. 1;H304 |
| Carbon dioxide | Dry ice / CARBON DIOXIDE | CAS-No.: 124-38-9 | 0.5 - 1.5 | Press. Gas (Comp.);H280 |

Comments : *Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

SECTION 4: First-aid measures

4.1. Description of first aid measures

| | |
|---------------------------------------|--|
| First-aid measures after inhalation | : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell. |
| First-aid measures after skin contact | : If irritation occurs, flush skin with plenty of water. Get medical attention if irritation persists. |
| First-aid measures after eye contact | : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. If easy to do, remove contact lenses, if worn. If irritation persists, get medical attention. |
| First-aid measures after ingestion | : IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting. |

Chain and Cable Lube

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

4.2. Most important symptoms and effects (acute and delayed)

| | |
|-------------------------------------|--|
| Symptoms/effects after inhalation | : May cause respiratory irritation. |
| Symptoms/effects after skin contact | : May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin. |
| Symptoms/effects after eye contact | : May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling. |
| Symptoms/effects after ingestion | : May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea or vomiting. |

4.3. Immediate medical attention and special treatment, if necessary

| | |
|-----------------------------------|---|
| Other medical advice or treatment | : Symptoms may not appear immediately. In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible). |
|-----------------------------------|---|

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

| | |
|------------------------------|---|
| Suitable extinguishing media | : Carbon dioxide, dry chemical, halons. Foam. |
|------------------------------|---|

5.2. Unsuitable extinguishing media

| | |
|--------------------------------|-------------------------|
| Unsuitable extinguishing media | : Do not use water jet. |
|--------------------------------|-------------------------|

5.3. Specific hazards arising from the hazardous product

| | |
|------------------|--|
| Fire hazard | : Flammable aerosol. Products of combustion may include, and are not limited to: oxides of carbon. Oxides of nitrogen. |
| Explosion hazard | : Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries. |

5.4. Special protective equipment and precautions for fire-fighters

| | |
|--------------------------------|--|
| Firefighting instructions | : DO NOT fight fire when fire reaches explosives. Evacuate area. |
| Protection during firefighting | : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA). Vapors may be heavier than air and may travel along the ground to a distant ignition source and flash back. Use water spray to keep fire-exposed containers cool. |

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

| | |
|------------------|--|
| General measures | : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Isolate from fire, if possible, without unnecessary risk. Remove ignition sources. Use special care to avoid static electric charges. |
|------------------|--|

6.2. Methods and materials for containment and cleaning up

| | |
|-------------------------|---|
| For containment | : Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE). |
| Methods for cleaning up | : Scoop up material and place in a disposal container. Provide ventilation. |

6.3. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

Chain and Cable Lube

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

SECTION 7: Handling and storage

7.1. Precautions for safe handling

| | |
|-----------------------------------|---|
| Precautions for safe handling | : Do not spray on an open flame or other ignition source. Keep away from sources of ignition - No smoking. Use non-sparking tools. Use explosion-proof equipment. Take precautionary measures against static discharge. Avoid contact with skin and eyes. Do not swallow. Do not breathe gas, fumes, vapour or spray. When using do not eat, drink or smoke. Use only outdoors or in a well-ventilated area. Do not pierce or burn, even after use. |
| Hygiene measures | : Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking. |
| Additional hazards when processed | : Hazardous waste due to potential risk of explosion. Do not pierce or burn, even after use. Keep away from sources of ignition - No smoking. |

7.2. Conditions for safe storage, including any incompatibilities

| | |
|--------------------|---|
| Technical measures | : Proper grounding procedures to avoid static electricity should be followed. |
| Storage conditions | : Keep locked up and out of reach of children. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store away from direct sunlight or other heat sources. Keep in fireproof place. |
| Storage area | : Store in a well-ventilated place. |

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

| Carbon dioxide (124-38-9) | |
|--|------------------------|
| USA - ACGIH - Occupational Exposure Limits | |
| ACGIH OEL TWA [ppm] | 5000 ppm |
| ACGIH OEL STEL [ppm] | 30000 ppm |
| USA - OSHA - Occupational Exposure Limits | |
| OSHA PEL (TWA) [1] | 9000 mg/m ³ |
| OSHA PEL (TWA) [2] | 5000 ppm |

8.2. Appropriate engineering controls

| | |
|----------------------------------|--|
| Appropriate engineering controls | : Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits. |
| Environmental exposure controls | : Maintain levels below Community environmental protection thresholds. |

8.3. Individual protection measures/Personal protective equipment

| |
|---|
| Hand protection: |
| Wear chemically resistant protective gloves. |
| Eye protection: |
| Safety glasses or goggles are recommended when using product. |
| Skin and body protection: |
| Wear suitable protective clothing |

Chain and Cable Lube

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Other information:

Do not eat, smoke or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking. Handle according to established industrial hygiene and safety practices.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|---|--------------------------|
| Physical state | : Liquid |
| Appearance | : Hazy. Liquid. Aerosol. |
| Color | : milky |
| Odor | : Mild aliphatic |
| Odor threshold | : No data available |
| pH | : No data available |
| Relative evaporation rate (butyl acetate=1) | : No data available |
| Relative evaporation rate (ether=1) | : No data available |
| Melting point | : No data available |
| Freezing point | : No data available |
| Boiling point | : 193°C (380 °F) |
| Flash point | : 64 °C (148 °F) |
| Auto-ignition temperature | : No data available |
| Decomposition temperature | : No data available |
| Flammability | : Flammable aerosol |
| Vapor pressure | : No data available |
| Relative vapor density at 20 °C | : No data available |
| Relative density | : 0.84 |
| Solubility | : No data available |
| Partition coefficient n-octanol/water | : No data available |
| Viscosity, kinematic | : No data available |
| Explosion limits | : No data available |

9.2. Other information

| | |
|--------------------|-------------|
| Heat of Combustion | : 49.7 kJ/g |
| Flame Projection | : 0 inches |
| Flashback | : None |

SECTION 10: Stability and reactivity

| | |
|------------------------------------|---|
| Reactivity | : No dangerous reaction known under conditions of normal use. |
| Chemical stability | : Stable under normal storage conditions. Flammable aerosol. Contents under pressure. Container may explode if heated. Do not puncture. Do not burn. Extreme risk of explosion by shock, friction, fire or other sources of ignition. |
| Possibility of hazardous reactions | : No dangerous reaction known under conditions of normal use. |
| Conditions to avoid | : Sources of ignition. Heat. Incompatible materials. |
| Incompatible materials | : Strong oxidizing agents. |
| Hazardous decomposition products | : May include, and are not limited to: oxides of carbon. Oxides of nitrogen. |
| Hardening time: | : No additional information available |

Chain and Cable Lube

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified.

Petroleum distillates, hydrotreated light (64742-47-8)

| | |
|---------------------|---------------|
| LD50 oral rat | > 5000 mg/kg |
| LD50 dermal rabbit | > 2000 mg/kg |
| LC50 inhalation rat | > 5.2 mg/l/4h |

Distillates, petroleum, hydrotreated light naphthenic (64742-53-6)

| | |
|---------------------|---|
| LD50 oral rat | > 5000 mg/kg |
| LD50 dermal rabbit | > 2000 mg/kg |
| LC50 inhalation rat | 2180 mg/m ³ (Exposure time: 4 h) |
| ATE CA (vapors) | 2.18 mg/l/4h |
| ATE CA (dust,mist) | 2.18 mg/l/4h |

Skin corrosion/irritation : Not classified
Serious eye damage/irritation : Not classified
Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified

Petroleum distillates, hydrotreated light (64742-47-8)

| | |
|---------------------------|--|
| NOAEL (animal/male, F0/P) | ≥ 3000 mg/kg body weight Animal: rat, Animal sex: male |
| STOT-single exposure | : Not classified |
| STOT-repeated exposure | : Not classified |

Petroleum distillates, hydrotreated light (64742-47-8)

| | |
|--------------------------------------|--|
| NOAEL (oral,rat,90 days) | 750 mg/kg body weight Animal: rat, Animal sex: female |
| NOAEC (inhalation,rat,vapor,90 days) | ≥ 0.024 mg/l air Animal: rat, Guideline: OECD Guideline 412 (Subacute Inhalation Toxicity: 28-Day Study) |

Distillates, petroleum, hydrotreated light naphthenic (64742-53-6)

| | |
|-----------------------------------|--|
| LOAEL (oral,rat,90 days) | 125 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents) |
| NOAEL (dermal,rat/rabbit,90 days) | ≈ 1000 mg/kg body weight Animal: rabbit, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study) |

Aspiration hazard : May be fatal if swallowed and enters airways.

Chain and Cable Lube

| | |
|-----------|---------|
| Vaporizer | Aerosol |
|-----------|---------|

Symptoms/effects after inhalation : May cause respiratory irritation.
Symptoms/effects after skin contact : May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.
Symptoms/effects after eye contact : May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
Symptoms/effects after ingestion : May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea or vomiting.

Chain and Cable Lube

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Other information : Likely routes of exposure: ingestion, inhalation, skin and eye.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : May be toxic to aquatic life.
Hazardous to the aquatic environment, short-term (acute) : Not classified
Hazardous to the aquatic environment, long-term (chronic) : Not classified

Petroleum distillates, hydrotreated light (64742-47-8)

| | |
|-----------------|---|
| LC50 - Fish [1] | 45 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through]) |
| LC50 - Fish [2] | 2.2 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static]) |
| BCF - Fish [1] | 61 – 159 |

Carbon dioxide (124-38-9)

| | |
|----------------|----------------------|
| BCF - Fish [1] | (no bioaccumulation) |
|----------------|----------------------|

Distillates, petroleum, hydrotreated light naphthenic (64742-53-6)

| | |
|----------------------|--|
| LC50 - Fish [1] | > 5000 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss) |
| EC50 - Crustacea [1] | > 1000 mg/l (Exposure time: 48 h - Species: Daphnia magna) |

12.2. Persistence and degradability

Chain and Cable Lube

| | |
|-------------------------------|------------------|
| Persistence and degradability | Not established. |
|-------------------------------|------------------|

12.3. Bioaccumulative potential

Chain and Cable Lube

| | |
|---------------------------|------------------|
| Bioaccumulative potential | Not established. |
|---------------------------|------------------|

Petroleum distillates, hydrotreated light (64742-47-8)

| | |
|----------------|----------|
| BCF - Fish [1] | 61 – 159 |
|----------------|----------|

Carbon dioxide (124-38-9)

| | |
|----------------|----------------------|
| BCF - Fish [1] | (no bioaccumulation) |
|----------------|----------------------|

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Ozone : Not classified

SECTION 13: Disposal considerations

13.1. Disposal methods

Product/Packaging disposal recommendations : This material must be disposed of in accordance with all local, state, provincial, and federal regulations. The generation of waste should be avoided or minimized wherever possible.

Chain and Cable Lube

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Additional information : Flammable vapors may accumulate in the container.

SECTION 14: Transport information

In accordance with TDG

14.1. UN number

UN-No. (TDG) : UN1950

14.2. UN proper shipping name

Proper Shipping Name (TDG) : AEROSOLS (flammable); Limited Quantity

14.3. Transport hazard class(es)

TDG

Transport hazard class(es) (TDG) : 2.1

Hazard labels (TDG) : 2.1



14.4. Packing group

Packing group (TDG) : Not applicable

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

Special transport precautions : Do not handle until all safety precautions have been read and understood.

TDG

UN-No. (TDG) : UN1950

TDG Special Provisions : 80 - Despite section 1.17 of Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases), a person must not offer for transport or transport these dangerous goods unless they are in a means of containment that is in compliance with the requirements for transporting gases in Part 5 (Means of Containment), 107 - (1) These Regulations, except for Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases) and Part 2 (Classification), do not apply to the handling, offering for transport or transporting of UN1950, AEROSOLS, and UN2037, GAS CARTRIDGES, that contain dangerous goods included in Class 2.1 or Class 2.2 and that are transported on a road vehicle, a railway vehicle or a vessel on a domestic voyage, if the aerosols or gas cartridges have a capacity less than or equal to 50 mL.
(2) Subsection (1) does not apply to self-defence spray.

Explosive Limit and Limited Quantity Index : 1 L

Excepted quantities (TDG) : E0

Passenger Carrying Road Vehicle or Passenger : 75 L

Carrying Railway Vehicle Index

Emergency Response Guide (ERG) Number : 126

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

Chain and Cable Lube

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

SECTION 15: Regulatory information

15.1. National regulations

All components of this product are listed, or excluded from listing, on the Canadian DSL (Domestic Substances List) and NDSL (Non-Domestic Substances List) inventories.

15.2. International regulations

No additional information available

SECTION 16: Other information

| | |
|-------------------|--------------|
| Issue date | : 11/19/2016 |
| Revision date | : 06/09/2022 |
| Other information | : None. |

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.