

HEAVY-DUTY CORROSION STOP



UPDATED: 5/10/2021

PART#	NET WT.	UPC	CASE QTY.
16-CSP	11oz/311g	0-32167-99009-2	6
Lubricates and Protects from Rust and Corrosion			

DESCRIPTION:

B'laster Corrosion Stop protects metal surfaces by leaving a protective film. It penetrates and resists water, displaces moisture and prevents further corrosion.

B'LAST ON:

Machined parts, Fasteners, Electrical Wiring, Battery Terminals & Connections, Padlocks, Trailers & Hitches, Outdoor Equipment, Gates & Hinges. In addition, Auto Frames, Firearms, Antiques, Engine Components, and Cast Iron Parts

DIRECTIONS FOR USE:

Shake the can well before using. Spray surface liberally and don't be shy about it. Several thin layers of product provides the best surface coverage and protection. It is suggested that the can be at room temperature when dispensing.

SAFETY:

DANGER! CONTENTS ARE FLAMMABLE: Keep spray away from heat, sparks, open flames, pilot lights, etc. Always unplug electrical tools, motors, and appliances before spraying or bringing can near any source of electricity.

Exposure Symptoms:

Inhalation: Remove exposed individual to fresh air, protecting yourself. Restore breathing if necessary. Contact a physician.

Skin Contact: Wash with soap and water. Remove any contaminated clothing and laundry before reusing. If irritation persists, seek medical attention.

Eye Contact: Flush with warm water for 15 minutes. Seek medical attention.

Ingestion: Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

TYPICAL PROPERTIES:

Flash Point: 0°F (-18°C)

Density (20°C): <8.34 lbs/gal

Specific Gravity (20°C): <1

Boiling Point: Not Determined

Product Category:

Other Vehicle and Marine Vessel Maintenance and Repair Products

Body Shop Safe: Yes

Base Type: Petroleum

Appearance: Milky White

Spray Pattern: Conical (Cone-Shaped)

Odor: Petroleum

Temperature Range: -20 to 150°F

Clean-Procedures: Start by scraping or wiping off excess product. Product can be removed with hot water and dish washing detergent. Use standard prep solvent to remove product prior to painting.