

FOOD GRADE CONVEYOR TRACK & CABLE LUBRICANT



UPDATED: 5/10/2021

PART#	NET WT.	UPC	CASE QTY.
16-CTC-FG	11oz/311g	0-32167-71005-8	6
Reduces Friction and Wear, Quiets Noisy Operation			

DESCRIPTION:

B'laster Conveyor Track & Cable Lubricant is a silicone-based lubricant for long-lasting lubrication. It leaves a tack-free film that won't accumulate dust and dirt. In some instances, its extreme pressure agents make it a suitable replacement for grease. Formulated for use on overhead doors and mechanisms, roller drives and conveyor equipment. NSF H1 registered.

B'LAST ON:

Bearings, Bushings, Cables, Chains, Conveyor Equipment, Door Tracks, Hinges, Overhead Door Mechanisms, Rollers, Springs, Window Tracks

DIRECTIONS FOR USE:

Hey, shake the can! Spray directly on equipment. Apply regularly to ensure proper protection. Consult owner's manuals before use on garage door opener drivers. Product contains silicone.

SAFETY:

DANGER! CONTENTS ARE FLAMMABLE: Keep spray away from heat, sparks, open flames, pilot lights, ect. Always unplug electrical tools, motors, and appliances before spraying or bringing can near any source of electricity.

Exposure Symptoms:

Inhalation: Move person to fresh air. If breathing is labored, administer oxygen. If symptoms develop, obtain medical attention.

Skin Contact: Wash affected skin with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

Eye Contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, get medical advice/attention.

Ingestion: Do not give anything by mouth to an unconscious person. Seek medical treatment. Do NOT induce vomiting.

TYPICAL PROPERTIES:

Flash Point: >205°F (> 96°C)

Density (20°C): 6.79 lbs/gal

Specific Gravity (20°C): 0.81

Boiling Point: >392°F (>200°C)

Product Category:

Silicone-Based Multi-Purpose Lubricant

Body Shop Safe: N/A

Base Type: Silicone

Appearance: Clear Colorless

Spray Pattern: Conical (Cone-Shaped)

Odor: Petroleum

Temperature Range: -20 to 200°F

VOC: < 60%

Clean-Procedures: Cover spills with inert absorbent material. Transfer to a container for disposal or recovery.