

PROFESSIONAL AIR TOOL CONDITIONER



UPDATED: 5/10/2021

PART#	NET WT.	UPC	CASE QTY.
16-ATC	11oz/311g	0-32167-10006-4	12
ATC-TS	3.5oz/99g	0-32167-15006-9	12
16-ATC-S	16 fl oz/473mL	0-32167-10020-0	12
128-ATC	1gal/3.8L	0-32167-10019-4	4
5-ATC	5gal/18.9L	0-32167-10028-6	1
55-ATC	55gal/208L	0-32167-60055-7	1

Cleans and Restores Pneumatic Tools

DESCRIPTION:

B'laster Air Tool Conditioner thoroughly cleans internal pneumatic tool parts, restoring them to peak performance and prolonging tool life. It breaks loose deposits that create friction and impede smooth operation. It also provides long-lasting lubrication and protects tools from freeze up.

B'LAST ON:

Impact Wrenches, Ratchets, Deburring Tools, Chisels, Sanders and Buffers, Polishers, Drills, Jackhammers and Pavement Breakers, Grinders, Most Pneumatic Equipment

DIRECTIONS FOR USE:

Shake the can well before using. First Application: Spray 3-5 seconds into tool's air supply fitting. Then let sit for 15 minutes to allow the product to dissolve deposits on internal components. Reconnect the air supply to expel fluids and deposits through the exhaust port. After first application, use a lubricant (Recommended: B'laster Professional Air Tool Lubricant) regularly to prevent the formation of harmful deposits. It is suggested that the can be at room temperature when dispensing.

SAFETY:

DANGER: FLAMMABLE: Contains petroleum distillate. Do not puncture or incinerate container. Keep away from open flame. Do not expose to heat or store at temperatures above 120°F.

Exposure Symptoms:

Inhalation: Vapors may cause drowsiness and dizziness. May cause respiratory tract irritation.

Skin Contact: Causes skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of the skin. May cause sensitization by skin contact.

Eye Contact: Causes serious eye damage. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. May cause burns.

Ingestion: May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea or vomiting.

TYPICAL PROPERTIES:

- Flash Point:** 58°F (14°C)
- Density (20°C):** 7.1 lbs/gal
- Specific Gravity (20°C):** 0.86
- Boiling Point:** 180°F (82°C)
- Product Category:** Multi-Purpose Lubricant
- Body Shop Safe:** Yes
- Base Type:** Petroleum
- Appearance:** Red
- Spray Pattern:** Pin Point
- Odor:** Alcohol
- Temperature Range:** -40 to 140°F
- VOC:** < 10%
- Clean-Procedures:** Product can be removed with hot water and dish washing detergent.