

MAXIMUM HEAVY-DUTY GREASE

PART#	NET WT.	UPC	CASE QTY.
GR-14C-HDG	14oz/397g	0-32167-77005-2	10
Extreme Pressure Lubrication and Protection			



DESCRIPTION:

Formulated as a unique high-performance extreme pressure grease that won't drip under the most severe operating conditions. It provides excellent lubrication and corrosion protection, and prolongs equipment life by providing superior protection even under high temperatures up to 550°F (dropping point).

B'LAST ON:

Great for any equipment that demands a shear stable, high-load carrying, corrosion-resistant grease. Especially automotive, construction, mining and farm equipment.

DIRECTIONS FOR USE:

For use with standard 14oz grease guns. Remove plastic cap, insert tube into the barrel of grease gun. Lift tab and pull up on the foil sealed end of cartridge.

SAFETY:

DANGER! May cause eye and skin irritation. May be harmful if swallowed. Avoid contact with eyes, skin and clothing.

Exposure Symptoms:

Inhalation: Under normal conditions of intended use, this material is not expected to be inhalation hazard. If some symptom exists, remove to fresh air. If not breathing, give artificial respiration. Get medical attention.

Skin Contact: Remove contaminated clothes. Flush exposed area with plenty of water followed by washing by soap, if available. If persistent irritation occurs, obtain medical attention. If product is injected into or under the skin due to any reason, the victim, regardless of size or appearance of wound, should be brought immediately to medical attention for emergency surgical needs. Though the initial symptoms due to high pressure injection may be minimal/absent, early surgical treatment may significantly reduce the extent of injury.

Eye Contact: Immediately flush with large quantities of cool water for at least 15 minutes including under eyelids. Keep eye wide open while rinsing. If symptoms persist get medical attention.

Ingestion: Drink plenty of water. In general no treatment is necessary unless large quantities are swallowed; however, it's advisable to take medical attention. Do not induce vomiting unless directed by medical personnel. Do not give anything by mouth to an unconscious person.

TYPICAL PROPERTIES:

Flash Point: 496°F (257°C)

Density (20°C): 7.8 lbs/gal

Specific Gravity (20°C): 0.94

Boiling Point: N/A

Product Category: Multi-Purpose Lubricant

Body Shop Safe: Yes

Base Type: Calcium Sulfonate Complex

Appearance: Green

Spray Pattern: N/A

Odor: Slight Petroleum

Temperature Range: -20 to 550°F

VOC: < 10%

Clean-Procedures: Start by scraping or wiping off excess product. Product can be removed with hot water and dish washing detergent. Use standard prep solvent to remove product prior to painting.

WARNING:

This product can expose you to chemicals including Naphthalene, which is known to the State of California to cause cancer, and Hexane, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.



UPDATED: 5/10/2021