

WATERPROOF MARINE GREASE



UPDATED: 5/10/2021

PART#	NET WT.	UPC	CASE QTY.
GR-14C-WP	14oz/397g	0-32167-77002-1	10
Long-Lasting Lubrication for Severe Marine Application			

DESCRIPTION:

Formulated to provide long-lasting surface protection even with prolonged exposure to saltwater. This unique calcium sulfonate grease has outstanding water wash-out performance, making it virtually waterproof and superior to competitor brands. Great for various marine applications, shipyard & dock equipment, outboard motors, winches & any applications exposed to wet conditions.

B'LAST ON:

Great for various marine applications, shipyard and dock equipment, outboard motors, winches and any applications exposed to wet conditions

DIRECTIONS FOR USE:

For use with standard 14oz grease guns. Remove plastic cap, insert tube into the barrel of grease gun. Lift tab and pull up on the foil sealed end of cartridge.

SAFETY:

DANGER! May cause eye and skin irritation. May be harmful if swallowed. Avoid contact with eyes, skin and clothing

Exposure Symptoms:

Inhalation: Under normal conditions of intended use, this material is not expected to be inhalation hazard. If some symptom exists, remove to fresh air. If not breathing, give artificial respiration. Get medical attention.

Skin Contact: Remove contaminated clothes. Flush exposed area with plenty of water followed by washing by soap, if available. If persistent irritation occurs, obtain medical attention. If product is injected into or under the skin due to any reason, the victim, regardless of size or appearance of wound, should be brought immediately to medical attention for emergency surgical needs. Though the initial symptoms due to high pressure injection may be minimal/absent, early surgical treatment may significantly reduce the extent of injury.

Eye Contact: Immediately flush with large quantities of cool water for at least 15 minutes including under eyelids. Keep eye wide open while rinsing. If symptoms persist get medical attention.

Ingestion: Drink plenty of water. In general no treatment is necessary unless large quantities are swallowed; however, it's advisable to take medical attention. Do not induce vomiting unless directed by medical personnel. Do not give anything by mouth to an unconscious person.

TYPICAL PROPERTIES:

Flash Point: 495°F (257°C)

Density (20°C): 7.8 lbs/gal

Specific Gravity (20°C): 0.94

Boiling Point: N/A

Product Category: Multi-Purpose Lubricant

Body Shop Safe: Yes

Base Type: Calcium Sulfonate Complex

Appearance: Blue

Spray Pattern: N/A

Odor: Slight Petroleum

Temperature Range: -20 to 550°F

VOC: < 10%

Clean-Procedures: Start by scraping or wiping off excess product. Product can be removed with hot water and dish washing detergent. Use standard prep solvent to remove product prior to painting.

WARNING:

This product can expose you to chemicals including Naphthalene, which is known to the State of California to cause cancer, and Hexane, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.