

ORIGINAL PB® PENETRATING GREASE

PART#	NET WT.	UPC	CASE QTY.
GR-14C-PB	14oz/397g	0-32167-77001-4	10
Lubricates, Penetrates and Protects from Rust and Corrosion			



UPDATED: 5/10/2021

DESCRIPTION:

A high-quality lithium grease harnessing the power of the Original PB B'laster creating a time-released penetrating action. This unique combination has the ability to penetrate existing rust and corrosion, but also stay on metal surfaces longer than conventional greases providing long-lasting lubrication and protection against rust and corrosion.

B'LAST ON:

Farm & Agriculture, landscaping, construction, automotive & recreational. It is also great for restoration and anything rusted or corroded.

Also good for: brake caliper pins, drum brake components

DIRECTIONS FOR USE:

BRUSH TOP: Brush liberally on rusted and corroded parts or surfaces. Relax and enjoy the time-release penetrating action. Repeat if necessary. After use, clean brush applicator with a cloth and store with the cap securely closed.

CARTRIDGE: For use with standard 14oz grease guns. Remove plastic cap, insert tube into the barrel of grease gun. Lift tab and pull up on the foil sealed end of cartridge.

SAFETY:

DANGER! May cause eye and skin irritation. Harmful if swallowed. Avoid contact with eyes, skin and clothing

Exposure Symptoms:

Inhalation: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention following exposure or if feeling unwell. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Skin Contact: Wash with plenty of soap and water. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 20 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Eye Contact: Wash with plenty of soap and water. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 20 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion: Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention following exposure or if feeling unwell. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

TYPICAL PROPERTIES:

Flash Point: 345°F (174°C)

Density (20°C): 7.73 lbs/gal

Specific Gravity (20°C): 0.93

Boiling Point: N/A

Product Category:
Multi-Purpose Lubricant

Body Shop Safe: Yes

Base Type: Synthetic

Appearance: Orange

Spray Pattern: N/A

Odor: Moderate Aromatic

Temperature Range: -20 to 550°F

VOC: < 10%

Clean-Procedures: Start by scraping or wiping off excess product. Product can be removed with hot water and dish washing detergent. Use standard prep solvent to remove product prior to painting.

WARNING:

This product can expose you to chemicals including Naphthalene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.