

Hydraulic Jack Oil

:

~

Safety Data Sheet according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Date of issue: 07/08/2021 Revision date: NA Version: 1.0

SECTION 1: Identification of the sub	stance/mixture and of the company/undertaking
1.1. Product identifier	
Product name	: Hydraulic Jack Oil
Product code	: 32-HJO
1.2. Relevant identified uses of the subst	ance or mixture and uses advised against
Use of the substance/mixture	: Multi-Purpose Lubricant
1.3. Details of the supplier of the safety d	ata sheet
The Blaster Corporation 8500 Sweet Valley Drive Valley View, Ohio 44125 - USA T (216) 901-5800 - F (216) 901-5801 www.blasterproducts.com	
1.4. Emergency telephone number Emergency number	: Chemtrec (800) 424-9300
	. Onemace (000) 424 3300
SECTION 2: Hazards identification	
2.1. Classification of the substance or mixture	
GHS-US classification Skin irritation 2 Specific target organ toxicity - Repeated exposur Aspiration toxicity 1	re 2
2.2. Label elements	

GHS-US labelling

This product is a consumer product and is labeled in accordance with the US Consumer Product Safety Commission regulations which take precedence over OSHA Hazard Communication labeling. The actual container label will not include the label elements below. The labeling below applies to industrial/professional products.

Hazard pictograms (GHS-US)

	GHS07 GHS08	
Signal word (GHS-US)	: Danger	
Hazard statements (GHS-US)	: Causes skin irritation. May cause damage to organs through prolonged or repeated exposure. May be fatal if swallowed and enters airways.	
Precautionary statements (GHS-US)	Wash hands thoroughly after handling. Wear protective gloves. Do not breathe dust/fume/gas/mist/vapors/spray. Get medical advice/attention if you feel unwell. If on skin: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations.	

Other hazards 2.3.

No additional information available

3.1. Substance

Not applicable

3.2. Mixture			
Name	Product identifier	%	GHS-US classification
White mineral oil, petroleum	(CAS No) 8042-47-5	60 - 100	Not classified
Distillates, petroleum, hydrotreated middle	(CAS No) 64742-46-7	7 - 13	Flam. Liq. 4 Acute Tox. 4 (Inhalation:dust,mist) Skin Irrit. 2 STOT RE 2 Asp. Tox. 1
Distillates, petroleum, hydrotreated light naphthenic	(CAS No) 64742-53-6	3 - 7	Asp. Tox. 1 Acute Tox. 4 (dust/mist) Carc. 1B

* The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200. EN (English)

07/08/2021

Page 1

Hydraulic Jack Oil

Safety Data Sheet according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

SECTION 4: First aid measures	
4.1. Description of first aid measures	
First-aid measures after inhalation	If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.
First-aid measures after skin contact	In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Call a physician if irritation develops and persists.
First-aid measures after eye contact	: In case of contact, immediately flush eyes with plenty of water. Remove contact lenses, if worn. If irritation persists, get medical attention.
First-aid measures after ingestion	: Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Immediately call a POISON CENTER or doctor/physician.
4.2. Most important symptoms and effect	s, both acute and delayed
Symptoms/injuries after inhalation	: May cause respiratory tract irritation.
Symptoms/injuries after skin contact	: Causes skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of the skin.
Symptoms/injuries after eye contact	: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
Symptoms/injuries after ingestion	: May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea or vomiting.
4.3. Indication of any immediate medical	attention and special treatment needed

Symptoms may not appear immediately. In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).

SECTION 5: Firefighting measures	
5.1. Extinguishing media	
Suitable extinguishing media	: Water fog, carbon dioxide, dry chemical or alcohol foam.
Unsuitable extinguishing media	: None known.
5.2. Special hazards arising from the sub	stance or mixture
Fire hazard	: Products of combustion may include, and are not limited to: oxides of carbon, hydrocarbons.
5.3. Advice for firefighters	
Protection during firefighting	: Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

SECTION 6: Accidental release measures			
6.1.	1. Personal precautions, protective equipment and emergency procedures		
General	measures	: Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.	
6.2.	Methods and material for containment	and cleaning up	
For conta	ainment	: Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).	
Methods	for cleaning up	: Scoop up material and place in a disposal container. Provide ventilation.	
6.3.	Reference to other sections		

See section 8 for further information on protective clothing and equipment and section 13 for advice on waste disposal.

SECTI	ON 7: Handling and stora	ge
7.1.	Precautions for safe handling	
Precautions for safe handling : Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapors/ spray. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke.		: Avoid contact with skin and eyes. Do not breathe dust/fume/gas/mist/vapors/ spray. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke.
Hygiene	e measures	: Launder contaminated clothing before reuse. Wash hands before eating, drinking, or smoking.
7.2.	Conditions for safe storage, including any incompatibilities	
Storage	conditions	: Keep out of the reach of children. Keep container tightly closed and in a well-ventilated place. Keep cool.
7.3.	Specific end use(s)	
Not ava	ilable.	

07/08/2021



Hydraulic Jack Oil Safety Data Sheet according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

SECTION 8. Exposure o	ontrols/personalprotection		
SECTION 8: Exposure controls/personalprotection 8.1. Control parameters			
White mineral oil, petroleum(8042-47-5)		
USA ACGIH	ACGIH TWA	Not applicable	
USA OSHA	OSHA PEL (TWA)	Not applicable	
Distillates, petroleum, hydro	treated middle (64742-46-7)		
USA ACGIH	ACGIH TWA	Not applicable	
USA OSHA	OSHA PEL (TWA)	Not applicable	
Distillates, petroleum, hydrotreated light naphthenic (64742-53-6)			
USA ACGIH	ACGIH TWA (mg/m ³)	5 mg/m ³ (mist)	
USA OSHA	OSHA PEL (TWA) (mg/m³)	5 mg/m ³ (mist)	
8.2. Exposure controls			
Appropriate engineering controls	: Use ventilation adequate to keep expo recommended exposure limits.	: Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.	
Hand protection	: Wear chemically resistant protective gl	: Wear chemically resistant protective gloves.	
Eye protection	: Safety glasses or goggles are recomm	: Safety glasses or goggles are recommended when using product.	
Skin and body protection	: Wear suitable protective clothing.	: Wear suitable protective clothing.	
Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.			
Environmental exposure controls : Maintain levels below Community environmental protection thresholds.		ronmental protection thresholds.	
Other information : Do not eat, smoke, or drink where material is handled, processed or stored. Wash hands carefully before eating or smoking. Handle according to established industrial hygiene and safety practices.			

SECTION 9: Physical and chemicalproperties

9.1. Information on basic physical and	d chemical properties
Physical state	: Liquid
Appearance	Oily
Color	: No data available
Odor	: Petroleum
Odor threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: <1
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 371.1 - 460 °C (700 - 860°F)
Flash point	: >182.2 °C (>360°F)
Auto-ignition temperature	: > 315.6 °C (>600°F)
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not flammable
Vapor pressure	: No data available
Relative vapor density at 20 °C	: >1 (Air =1)
Relative density	: 0.86
Solubility	: Insoluble
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: 19 cSt @ 40°C (104°F)
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosive limits	: No data available

EN (English)

Hydraulic Jack Oil Safety Data Sheet

d (CER29 1910 1200) HazCom 2012

according to the Hazard Communication Standard (CFR29	1910.1200) HazCom 2012.		
9.2. Other information			
No additional information available			
SECTION 10: Stability and reactivity			
10.1. Reactivity			
	of normal use		
5	No dangerous reaction known under conditions of normal use.		
10.2. Chemical stability Stable under normal storage conditions.			
_			
10.3. Possibility of hazardous reactions			
No dangerous reaction known under conditions	of normal use.		
10.4. Conditions to avoid			
Heat. Excessive water.			
10.5. Incompatible materials			
Strong oxidizing agents. Strong reducing agents			
10.6. Hazardous decomposition products			
May include, and are not limited to: oxides of car	bon, hydrocarbons.		
SECTION 11: Toxicological informati	on		
11.1. Information on toxicological effects			
Acute toxicity	: Not classified		
Air Tool Lubricant			
LD50 oral rat	> 2000 mg/kg		
LD50 dermal rabbit	> 2000 mg/kg		
LC50 inhalation rat	No data available		
White mineral oil, petroleum(8042-47-5)			
LD50 oral rat	>5000 mg/kg		
LD50 dermal rabbit	>2000 mg/kg		
LC50 inhalation rat	> 5 mg/l/4h		
Distillates, petroleum, hydrotreated middle	(64742-46-7)		
LD50 oral rat	7400 mg/kg		
LD50 dermal rabbit	>2000 mg/kg		
LC50 inhalation rat	4.6 mg/l/4h		
Distillates, petroleum, hydrotreated light na	phthenic (64742-53-6)		
LD50 oral rat	>5000 mg/kg		
LD50 dermal rabbit	> 2000 mg/kg		
LC50 inhalation rat	2.18 mg/l/4h		
Skin corrosion/irritation	: Causes skin irritation.		
Serious eye damage/irritation	: Based on available data, the classification criteria are not met.		
Respiratory or skin sensitization	: Based on available data, the classification criteria are not met.		
Germ cell mutagenicity	: Based on available data, the classification criteria are not met.		
Carcinogenicity	: Based on available data, the classification criteria are not met.		
	· Read an available data, the electricities aritaria are not mat		
Reproductive toxicity Specific target organ toxicity (single exposure)	: Based on available data, the classification criteria are not met. : Based on available data, the classification criteria are not met.		
Specific target organ toxicity (repeated exposure)	: May cause damage to organs through prolonged or repeated exposure.		
Aspiration hazard	: May be fatal if swallowed and enters airways.		
Symptoms/injuries after inhalation	: May cause respiratory tract irritation.		
Symptoms/injuries after skin contact	: Causes skin irritation. Symptoms may include redness, edema, drying, defatting and cracking of the skin.		
Symptoms/injuries after eye contact	: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.		

EN (English)



Hydraulic Jack Oil

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Symptoms/injuries after ingestion

: May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea or vomiting.

	cause chemical pheumonius. May cause stomach distress, hausea or vorniung.
SECTION 12: Ecological informatio	n
12.1. Toxicity	
Ecology - general	: May cause long-term adverse effects in the aquatic environment.
12.2. Persistence and degradability	
Air Tool Lubricant	
Persistence and degradability	Not established.
12.3. Bioaccumulative potential	
Air Tool Lubricant	
Bioaccumulative potential	Not established.
12.4. Mobility in soil	
No additional information available	
12.5. Other adverse effects	
Effect on ozone layer	: No additional information available
Effect on the global warming	: No known ecological damage caused by this product.
OFOTION 42 Discussion data	
SECTION 13: Disposal consideration	DNS
13.1. Waste treatment methods Waste disposal recommendations Image: Commendation state	: This material must be disposed of in accordance with all local, state, provincial, and federal
waste disposal recommendations	regulations. The generation of waste should be avoided or minimized wherever possible.
SECTION 44. Transport information	
SECTION 14: Transport information In accordance with DOT	
14.1. UN number	
Not regulated for transport	
14.2. UN proper shipping name	
Not applicable	
14.3. Additional information	
Other information	: No supplementary information available.
Special transport precautions	: Do not handle until all safety precautions have been read and understood.
SECTION 15: Regulatory informatic	on service and s
15.1. US Federal regulations	
All components of this product are listed, or ex Substances Control Act (TSCA)inventory.	xcluded from listing, on the United States Environmental Protection Agency Toxic
15.2. US State regulations	
Air Tool Lubricant	
State or local regulations	This product does not contain a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.
SECTION 16: Other information	
SECTION 16: Other information	
Indication of changes	: None.
Date of issue Other information	: 07/08/2021 : None.
Calor montation	

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

EN (English)

