# **TECHNICAL DATA SHEET**

# FAST-ACTING LOCK DRY LUBRICANT & DE-ICER

PART#	NET WT.	UPC	CASE QTY.
LLD-TS	3oz/85g	0-32167-20024-5	12
Loosans and Lubricatos			

## Loosens and Lubricates

# DESCRIPTION:

B'laster Fast-Acting Lubricant & De-Icer is a dry lubricant that loosens and lubricates with a proprietary super-slip additive. It quickly frees up stuck or frozen locks in commercial, automotive, and marine applications and equipment. Its fast-acting dry fromula won't attract dirt.

#### **B'LAST ON:**

All Locks, including: Padlocks, Combination Locks, Door Locks, Vehicle Door Locks, Ignition Locks

## **DIRECTIONS FOR USE:**

Shake the can well before using. Spray area, let sit for a few minutes. Wipe off excess. It is suggested that the can be at room temperature when dispensing.

#### SAFETY:

**DANGER!:** Keep away from fire, sparks, heated surfaces, and other ignition sources. Use only in a well-ventilated area, as vapors may accumulate. Use added caution in confined area such as basements and automoble compartments.

#### **Exposure Symptoms:**

**Inhalation:** If inhaled: Remove person to fresh air and keep comfortable for breathing. If breathing is labored, administer oxygen. Call a POISON CENTER/doctor if you feel unwell.

**Skin Contact:** Wash affected skin with soap and water. If skin irritation occurs, get medical advice/attention. Take off contaminated clothing and wash it before reuse.

**Eye Contact:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

**Ingestion:** Do not give anything by mouth to an unconscious person. Seek medical treatment. Do NOT induce vomiting.

## **TYPICAL PROPERTIES:**

Flash Point: 54°F (12°C) Density (20°C): 6.55 lbs/gal Specific Gravity (20°C): 0.79 Boiling Point: 182°F (83°C) Product Category: Multi-Purpose Dry Lubricant Body Shop Safe: Yes Base Type: Isopropanol Appearance: Clear Colorless Spray Pattern: Conical (Cone-Shaped) Odor: Typical Petroleum Temperature Range: -20 to 120°F VOC: < 100% Clean-Procedures: Product can be

removed with hot water and dish washing

detergent.



UPDATED: 4/12/2022