

PRO-GRADE MULTI-PURPOSE LUBRICANT



UPDATED: 4/12/2022

PART#	NET WT.	UPC	CASE QTY.
PB-50	8oz/227g	0-32167-00050-0	12
PB-50-128	1 gal	0-32167-50128-1	4
PB-50-TS	3oz/85g	0-32167-00058-6	12
55-PB50	55gal/208L	0-32167-05055-0	1

Lubricates, Protects and Displaces Moisture

DESCRIPTION:

B'laster Multi-Purpose Lubricant is a high-performance formula designed to lubricate moving parts in and around the house such as window tracks, hinges, chains, glides and gears. Formulated with a proprietary super-slip additive to help reduce friction and wear, enhance performance and protect surfaces. It outperforms leading competitors and prevents rust and further corrosion on car parts, fishing reels and tackle, all tools, firearms, sports equipment, marine applications and more.

B'LAST ON:

Window & Door Tracks, Hinges, Valves, Wheels, Rollers, Glides, Chains, Gears, Car Parts, Fishing Tackle, Firearms, Recreation & Sports Equipment, Hand Tools, Nuts & Bolts, Dials, Locks, Engines, Marine Applications, Agriculture Equipment, Lawn & Garden Tools & More!

DIRECTIONS FOR USE:

Shake the can well before using. Spray area & let it sit. For best protection, do not wipe off. It is suggested that the can be at room temperature when dispensing.

SAFETY:

DANGER: CONTENTS ARE FLAMMABLE: Keep spray away from heat, sparks, open flames, pilot lights, etc. Always unplug electrical tools, motors, and appliances before spraying or bringing can near any source of electricity.

Exposure Symptoms:

Inhalation: May cause respiratory tract irritation.

Skin Contact: May cause skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.

Eye Contact: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.

Ingestion: May be fatal if swallowed and enters airways. This product may be aspirated into the lungs and cause chemical pneumonitis. May cause stomach distress, nausea or vomiting.

TYPICAL PROPERTIES:

Flash Point: 148°F (64°C)

Density (20°C): 6.9 lbs/gal

Specific Gravity (20°C): 0.82

Boiling Point: 380°F (193°C)

Product Category:

Multi-Purpose Lubricant

Body Shop Safe: No

Base Type: Petroleum

Appearance: Clear Colorless

Spray Pattern: Conical (Cone-Shaped)

Odor: Vanilla: Vanilla

VOC: < 10%

Temperature Range: -20 to 230°F

Clean-Procedures: Product can be removed with hot water and dish washing detergent. Use standard prep solvent to remove product prior to painting.