

TECHNICAL DATA SHEET



UPDATED: 2/16/2023

EXTRA TACKY RED GREASE

PART#	NET WT.	UPC	CASE QTY.
GR-14C-HTR	14oz/397g	0-32167-77004-5	10
GR-16T-HTR	16 fl oz	0-32167-77010-6	12
High-Temp Protection and Lubrication			

DESCRIPTION:

Extra Tacky Red grease is formulated with refined mineral base oils, hydroxy stearate lithium complex thickener and high-end additives. This combination enhances stickiness, anti-wear properties and rust & corrosion prevention. The addition of extreme pressure additives enhances performance in the most severe high-load, vibration, water contamination and high temperature applications.

BENEFITS:

- Exceptional anti-wear and anti-friction control
- Durable against high-loads, pressures and impacts
- High mechanical stability • Protects against water washout
- Smooth and stringy texture provides good pumpability
- High adhesion • Protects against rust and corrosion

B'LAST ON:

Great for heavy-duty applications for automotive, fleet, construction equipment, farm equipment, chassis and bearings.

DIRECTIONS FOR USE:

For use with standard 14oz grease guns. Remove plastic cap, insert tube into the barrel of grease gun. Lift tab and pull up on the foil sealed end of cartridge.

SAFETY:

DANGER! May cause eye and skin irritation. May be harmful if swallowed. Avoid contact with eyes, skin and clothing.

Exposure Symptoms:

Inhalation: Under normal conditions of intended use, this material is not expected to be inhalation hazard. If some symptom exists, remove to fresh air. If not breathing, give artificial respiration. Get medical attention.

Skin Contact: Remove contaminated clothes. Flush exposed area with plenty of water followed by washing by soap, if available. If persistent irritation occurs, obtain medical attention. If product is injected into or under the skin due to any reason, the victim, regardless of size or appearance of wound, should be brought immediately to medical attention for emergency surgical needs. Though the initial symptoms due to high pressure injection may be minimal/absent, early surgical treatment may significantly reduce the extent of injury.

Eye Contact: Immediately flush with large quantities of cool water for at least 15 minutes including under eyelids. Keep eye wide open while rinsing. If symptoms persist get medical attention.

Ingestion: Drink plenty of water. In general no treatment is necessary unless large quantities are swallowed; however, it's advisable to take medical attention. Do not induce vomiting unless directed by medical personnel. Do not give anything by mouth to an unconscious person.

CHARACTERISTICS:

NLGI Grade: 2

Thickener: Lithium complex

Color: Red

Texture: Tacky

Base oil viscosity @ 40°C, cSt: 220

Worked penetration @ 60 strokes mm/10 25°C: 280

Dropping point, °C: 288

Water washout @ 79°C, % weight loss, max: 5

Mechanical stability, % of loss: 5

Oil separation, %, max.: 5

Rust and corrosion resistance test: Pass

4-ball weld point, Kg: 315

Operating temperature, °C: -20 to 190

Specifications:

- NLGI GC-LB
- ASTM D4950

Clean-Procedures: Start by scraping or wiping off excess product. Product can be removed with hot water and dish washing detergent. Use standard prep solvent to remove product prior to painting.

WARNING:

WARNING: This product can expose you to chemicals including Hexane, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.