

PRO-GRADE MULTI-PURPOSE GREASE

PART#	NET WT.	UPC	CASE QTY.
GR-14C-MP	14oz/397g	0-32167-77003-8	10
High-Quality Lubrication and Corrosion Protection			



DESCRIPTION:

Pro-Grade Multi-Purpose grease is formulated with lithium hydroxy stearate, mineral base oils as well as antioxidant and anti-rust additives. This combination allows for enhanced performance in automotive and industrial applications.

BENEFITS:

- Protects against oxidation and corrosion
- Good pumpability
- Excellent mechanical stability
- Protects against water washout

B'LAST ON:

Great for the automotive, marine, construction, landscaping and farm industries. **Also good for:** recreational equipment and a variety of general purpose grease applications.

DIRECTIONS FOR USE:

For use with standard 14oz grease guns. Remove plastic cap, insert tube into the barrel of grease gun. Lift tab and pull up on the foil sealed end of cartridge.

SAFETY:

DANGER! May cause eye and skin irritation. May be harmful if swallowed. Avoid contact with eyes, skin and clothing

Exposure Symptoms:

Inhalation: Under normal conditions of intended use, this material is not expected to be inhalation hazard. If some symptom exists, remove to fresh air. If not breathing, give artificial respiration. Get medical attention.

Skin Contact: Remove contaminated clothes. Flush exposed area with plenty of water followed by washing by soap, if available. If persistent irritation occurs, obtain medical attention. If product is injected into or under the skin due to any reason, the victim, regardless of size or appearance of wound, should be brought immediately to medical attention for emergency surgical needs. Though the initial symptoms due to high pressure injection may be minimal/absent, early surgical treatment may significantly reduce the extent of injury.

Eye Contact: Immediately flush with large quantities of cool water for at least 15 minutes including under eyelids. Keep eye wide open while rinsing. If symptoms persist get medical attention.

Ingestion: Drink plenty of water. In general no treatment is necessary unless large quantities are swallowed; however, it's advisable to take medical attention. Do not induce vomiting unless directed by medical personnel. Do not give anything by mouth to an unconscious person.

CHARACTERISTICS:

NLGI Grade: 2

Thickener: Lithium

Color: Amber

Texture: Buttery

Worked penetration

@ 60 strokes 1/10 mm 25°C: 280

Dropping point, °C: 195

Water washout

@ 80°C, % weight loss, max: 5

Leakage tendencies,

% weight loss, max: 2

Oil separation, %, max.: 5

Timken load OK, lbs.: 40

4-ball weld point, Kg: 250

Specifications:

- NLGI GB, GA, LB, LA
- ASTM D4950
- SAE J310
- DIN 51825
- ISO 6743-9
- SAE J2695

Clean-Procedures: Start by scraping or wiping off excess product. Product can be removed with hot water and dish washing detergent. Use standard prep solvent to remove product prior to painting.



UPDATED: 2/16/2023