



SAFETY DATA SHEET

1. Identification

Product identifier B'laster Battery Terminal Cleaner & Protectant

Other means of identification

Part No. 16-BTCAP6/6

Tariff code 3402.20.5100

Recommended use Cleaner & Protectant

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name Blaster LLC
Address 8500 Sweet Valley Drive
Valley View, Ohio 44125 - USA
Telephone T (216)901-5800
F (216)901-5801
Website www.blastercorp.com

Emergency phone number : Chemtrec (800) 424-9300

2. Hazard(s) identification

Physical hazards Flammable aerosols Category 2

Health hazards Not classified.

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Warning

Hazard statement Flammable aerosol.

Precautionary statement

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

Response Wash hands after handling.

Storage Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal Dispose of waste and residues in accordance with local authority requirements.

Hazard(s) not otherwise classified (HNOC) None known.

Supplemental information NOTE: This product is a consumer product and is labeled in accordance with the US Consumer Product Safety Commission regulations which take precedence over OSHA Hazard Communication labeling. The container label may not include the OSHA label elements listed in this document. Always carefully review the entire SDS and the product label prior to use in the workplace.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Water		7732-18-5	80 - < 90

Material name: B'laster Battery Terminal Cleaner & Protectant

16-BTCAP6/6 Version #: 03 Revision date: 02-09-2023 Issue date: 07-08-2019

SDS US

1 / 11

Chemical name	Common name and synonyms	CAS number	%
Butane		106-97-8	5 - < 10
Butoxyethanol		111-76-2	1 - < 5
Propane		74-98-6	1 - < 5
Sodium Bicarbonate		144-55-8	1 - < 5
Methyl Orange		547-58-0	< 0.5
Ammonium Hydroxide		1336-21-6	< 0.1
Diethanolamine		111-42-2	< 0.1
FORMALDEHYDE		50-00-0	< 0.1
Triethanolamine		102-71-6	< 0.1

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation	If symptoms develop move victim to fresh air. Get medical attention if symptoms persist.
Skin contact	Wash off with soap and water. Get medical attention if irritation develops and persists.
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	In the unlikely event of swallowing contact a physician or poison control center.
Most important symptoms/effects, acute and delayed	Direct contact with eyes may cause temporary irritation.
Indication of immediate medical attention and special treatment needed	Treat symptomatically.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.
General fire hazards	Flammable aerosol.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Do not get in eyes, on skin, or on clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Level 1 Aerosol.

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Components	Type	Value
FORMALDEHYDE (CAS 50-00-0)	STEL	2 ppm
	TWA	0.75 ppm

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value
Ammonium Hydroxide (CAS 1336-21-6)	PEL	35 mg/m3
		50 ppm
Butoxyethanol (CAS 111-76-2)	PEL	240 mg/m3
		50 ppm
Propane (CAS 74-98-6)	PEL	1800 mg/m3
		1000 ppm

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Ammonium Hydroxide (CAS 1336-21-6)	STEL	35 ppm	
	TWA	25 ppm	
Butane (CAS 106-97-8)	STEL	1000 ppm	
Butoxyethanol (CAS 111-76-2)	TWA	20 ppm	
Diethanolamine (CAS 111-42-2)	TWA	1 mg/m3	Inhalable fraction and vapor.
FORMALDEHYDE (CAS 50-00-0)	STEL	0.3 ppm	
	TWA	0.1 ppm	
Triethanolamine (CAS 102-71-6)	TWA	5 mg/m3	

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Ammonium Hydroxide (CAS 1336-21-6)	STEL	27 mg/m3
		35 ppm
	TWA	18 mg/m3

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Butane (CAS 106-97-8)	TWA	25 ppm
		1900 mg/m3
Butoxyethanol (CAS 111-76-2)	TWA	800 ppm
		24 mg/m3
Diethanolamine (CAS 111-42-2)	TWA	5 ppm
		15 mg/m3
FORMALDEHYDE (CAS 50-00-0)	Ceiling	3 ppm
		0.1 ppm
Propane (CAS 74-98-6)	TWA	0.016 ppm
		1800 mg/m3
		1000 ppm

Biological limit values
ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Butoxyethanol (CAS 111-76-2)	200 mg/g	Butoxyacetic acid (BAA), with hydrolysis	Creatinine in urine	*

* - For sampling details, please see the source document.

Exposure guidelines
US - California OELs: Skin designation

Butoxyethanol (CAS 111-76-2)

Can be absorbed through the skin.

Diethanolamine (CAS 111-42-2)

Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

Butoxyethanol (CAS 111-76-2)

Skin designation applies.

US - Tennessee OELs: Skin designation

Butoxyethanol (CAS 111-76-2)

Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

Diethanolamine (CAS 111-42-2)

Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

Butoxyethanol (CAS 111-76-2)

Can be absorbed through the skin.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Butoxyethanol (CAS 111-76-2)

Can be absorbed through the skin.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment
Eye/face protection

Wear safety glasses with side shields (or goggles).

Skin protection
Hand protection

Wear appropriate chemical resistant gloves.

Other

Wear appropriate chemical resistant clothing.

Respiratory protection

If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator. Chemical respirator with organic vapor cartridge and full facepiece if threshold limits are exceeded.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance	Hazy
Physical state	Liquid.
Form	Aerosol.
Color	Orange.
Odor	Soapy
Odor threshold	Not available.
pH	8.5 - 9
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.
Flash point	-155.9 °F (-104.4 °C) Propellant estimated
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	3792.1165 - 5171.068 hPa (20 C)
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Aerosol spray enclosed space	
Deflagration density	< 300 g/m ³
Time equivalent	< 300 s/m ³
Density	8.8 lbs/gal (liquid)
Explosive properties	Not explosive.
Flame extension	0 no flame/no flashback
Flammability class	Flammable IB estimated
Heat of combustion (NFPA 30B)	5.39 kJ/g estimated
Oxidizing properties	Not oxidizing.
Percent volatile	> 93 % estimated
Specific gravity	1.055 estimated
VOC	< 12 %

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents. Chlorine. Fluorine. Nitrates.

Hazardous decomposition products

No hazardous decomposition products are known.

11. Toxicological information**Information on likely routes of exposure****Inhalation**

Prolonged inhalation may be harmful.

Skin contact

2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans.

Eye contact

Direct contact with eyes may cause temporary irritation.

Ingestion

Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Direct contact with eyes may cause temporary irritation.

Information on toxicological effects**Acute toxicity**

Not known.

Components**Species****Test Results**

Ammonium Hydroxide (CAS 1336-21-6)

Acute**Oral**

LD50

Rat

350 mg/kg

Butoxyethanol (CAS 111-76-2)

Acute**Dermal**

LD50

Rabbit

400 mg/kg

Oral

LD50

Rat

530 - 2800 mg/kg

Diethanolamine (CAS 111-42-2)

Acute**Oral**

LD50

Rat

710 mg/kg

FORMALDEHYDE (CAS 50-00-0)

Acute**Inhalation**

LC50

Rat

0.48 mg/l, 4 Hours

Oral

LD50

Rat

100 mg/kg

Sodium Bicarbonate (CAS 144-55-8)

Acute**Oral**

LD50

Rat

> 4000 mg/kg

Triethanolamine (CAS 102-71-6)

Acute**Dermal**

LD50

Rabbit

> 2000 mg/kg

Oral

LD50

Rat

6400 mg/kg

Skin corrosion/irritation

Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye irritation

Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

ACGIH sensitization

FORMALDEHYDE (CAS 50-00-0)

Dermal sensitization

Respiratory sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Butoxyethanol (CAS 111-76-2)

3 Not classifiable as to carcinogenicity to humans.

Diethanolamine (CAS 111-42-2)

2B Possibly carcinogenic to humans.

FORMALDEHYDE (CAS 50-00-0)

1 Carcinogenic to humans.

Triethanolamine (CAS 102-71-6)

3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

FORMALDEHYDE (CAS 50-00-0)

Cancer

US. National Toxicology Program (NTP) Report on Carcinogens

FORMALDEHYDE (CAS 50-00-0)

Known To Be Human Carcinogen.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity - single exposure Not classified.

Specific target organ toxicity - repeated exposure Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects May be harmful if absorbed through skin. Prolonged inhalation may be harmful.

2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components	Species	Test Results
Ammonium Hydroxide (CAS 1336-21-6)		
Aquatic		
Fish LC50	Western mosquitofish (<i>Gambusia affinis</i>)	15 mg/l, 96 hours
Butoxyethanol (CAS 111-76-2)		
Aquatic		
Fish LC50	Inland silverside (<i>Menidia beryllina</i>)	1250 mg/l, 96 hours
Diethanolamine (CAS 111-42-2)		
Aquatic		
Crustacea EC50	Water flea (<i>Ceriodaphnia dubia</i>)	61.8 - 86.04 mg/l, 48 hours
Fish LC50	Fathead minnow (<i>Pimephales promelas</i>)	100 mg/l, 96 hours
FORMALDEHYDE (CAS 50-00-0)		
Aquatic		
Crustacea EC50	Water flea (<i>Daphnia pulex</i>)	4.3 - 7.8 mg/l, 48 hours
Fish LC50	Striped bass (<i>Morone saxatilis</i>)	10.302 - 16.743 mg/l, 96 hours
Sodium Bicarbonate (CAS 144-55-8)		
Aquatic		
Fish LC50	Western mosquitofish (<i>Gambusia affinis</i>)	7550 mg/l, 96 hours
Triethanolamine (CAS 102-71-6)		
Aquatic		
Crustacea EC50	Water flea (<i>Ceriodaphnia dubia</i>)	565.2 - 658.3 mg/l, 48 hours

Components	Species	Test Results
Fish	LC50	Fathead minnow (Pimephales promelas) 10610 - 13010 mg/l, 96 hours
Persistence and degradability	No data is available on the degradability of any ingredients in the mixture.	
Bioaccumulative potential		
Partition coefficient n-octanol / water (log Kow)		
Butane		2.89
Butoxyethanol		0.83
Diethanolamine		-1.43
FORMALDEHYDE		0.35
Propane		2.36
Triethanolamine		-1
Mobility in soil	No data available.	
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.	

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Incinerate the material under controlled conditions in an approved incinerator. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	D001: Waste Flammable material with a flash point <140 F The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

14. Transport information

DOT

UN number	UN1950
UN proper shipping name	Aerosols, flammable, Limited Quantity
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Label(s)	2.1
Packing group	Not available.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Special provisions	N82
Packaging exceptions	306

IATA

UN number	UN1950
UN proper shipping name	Aerosols, flammable, Limited Quantity
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Packing group	Not available.
Environmental hazards	No.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

IMDG

UN number	UN1950
UN proper shipping name	AEROSOLS, Limited Quantity
Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Packing group	Not available.

Environmental hazards**Marine pollutant**

No.

EmS



F-D, S-U

Special precautions for user

Read safety instructions, SDS and emergency procedures before handling.

**Transport in bulk according to
Annex II of MARPOL 73/78 and
the IBC Code**

Not established.

DOT; IMDG**IATA****15. Regulatory information****US federal regulations**

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Ammonium Hydroxide (CAS 1336-21-6)	Listed.
Butane (CAS 106-97-8)	Listed.
Butoxyethanol (CAS 111-76-2)	Listed.
Diethanolamine (CAS 111-42-2)	Listed.
FORMALDEHYDE (CAS 50-00-0)	Listed.
Propane (CAS 74-98-6)	Listed.

SARA 304 Emergency release notification

FORMALDEHYDE (CAS 50-00-0) 100 LBS

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

FORMALDEHYDE (CAS 50-00-0)

Cancer
Skin sensitization
Respiratory sensitization
Eye irritation
Skin irritation
respiratory tract irritation
Acute toxicity
Flammability

Superfund Amendments and Reauthorization Act of 1986 (SARA)**SARA 302 Extremely hazardous substance**

Chemical name	CAS number	Reportable quantity (pounds)	Threshold planning quantity (pounds)	Threshold planning quantity, lower value (pounds)	Threshold planning quantity, upper value (pounds)
FORMALDEHYDE	50-00-0	100	500		

Material name: B'laster Battery Terminal Cleaner & Protectant

16-BTCAP6/6 Version #: 03 Revision date: 02-09-2023 Issue date: 07-08-2019

SDS US

9 / 11

Classified hazard categories Flammable (gases, aerosols, liquids, or solids)
Hazard not otherwise classified (HNOC)

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Butoxyethanol	111-76-2	1 - < 5
FORMALDEHYDE	50-00-0	< 0.1

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Diethanolamine (CAS 111-42-2)
FORMALDEHYDE (CAS 50-00-0)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Butane (CAS 106-97-8)
FORMALDEHYDE (CAS 50-00-0)
Propane (CAS 74-98-6)

Safe Drinking Water Act (SDWA) Not regulated.

US state regulations

California Proposition 65



WARNING: This product can expose you to chemicals including Diethanolamine, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

Diethanolamine (CAS 111-42-2) Listed: June 22, 2012
FORMALDEHYDE (CAS 50-00-0) Listed: January 1, 1988

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Butane (CAS 106-97-8)
Butoxyethanol (CAS 111-76-2)
Diethanolamine (CAS 111-42-2)
FORMALDEHYDE (CAS 50-00-0)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	07-08-2019
Revision date	02-09-2023
Version #	03
HMIS® ratings	Health: 0 Flammability: 4 Physical hazard: 0

Material name: B'laster Battery Terminal Cleaner & Protectant

16-BTCAP6/6 Version #: 03 Revision date: 02-09-2023 Issue date: 07-08-2019

SDS US

10 / 11

NFPA ratings

Health: 0
Flammability: 3
Instability: 0

NFPA ratings**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Revision information

Physical & Chemical Properties: Multiple Properties