

PB Clear Low Odor 20-PBCLO-DSF

1 PRODUCT AND COMPANY IDENTIFICATION

Product Identifier: PB-Clear No Odor 109362
Product Code: 20-PCLO-DSF
Revision Date: 7/3/2025
Chemical Family: Penetrant
Product Description: Light penetrating lubricant
Product Use: Use as recieved at ambient or slightly elevated temperatures.

Supplier Details: Blaster LLC
8500 Sweet Valley Dr.
Valley View, OH 44125

Phone: 201-901-5800
Web: www.blasterproducts.com
Emergency: Chemtrec (800) 424-9300

2 HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

GHS Classification in Accordance with 29 CFR 1910 (OSHA HCS):

Health, Aspiration hazard,
Category 1
Physical, Flammable Aerosol,
Category 2
Health, Specific target organ toxicity - Single exposure, Category 3
Gas Under Pressure: Compressed Gas

GHS Label Elements, Including Precautionary Statements

GHS Signal Word: **DANGER**

GHS Hazard Pictograms:



GHS Hazard Statements:

H223-Flammable aerosol
H280- Contains gas under pressure; may explode if heated
H304 - May be fatal if swallowed and enters airways
H283- Flammable chemical under pressure; May
explode if heated
H336 - May cause drowsiness or dizziness

GHS Precautionary Statements:

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P240 - Ground and bond container and receiving equipment.
P241 - Use explosion-proof [electrical/ventilating/lighting/...] equipment.
P243 - Take action to prevent static discharges.
P264 - Wash hands thoroughly after handling.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER/doctor/...
P331 - Do NOT induce vomiting.
P370 + P378 - In case of fire: Use Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 - Store in a well-ventilated place. Keep cool.
P501 - Dispose of contents/ container to an approved waste disposal plant.



PB Clear Low Odor 20-PBCLO-DSF

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

3 COMPOSITION/INFORMATION OF INGREDIENTS

Chemical Ingredients

CAS#	%	Chemical Name
68551-16-6	12-16%	Alkanes, C9-11-iso-
64742-53-6	48-55%	Distillates, petroleum, hydrotreated light naphthenic
64742-47-8	26-33%	Distillates, petroleum, hydrotreated light
57855-77-3	<0.4%	Naphthalenesulfonic acid, dinonyl-, calcium salt
132259-10-0	<0.5%	Compressed Air

4 FIRST AID MEASURES

- Inhalation:** First aid is not normally required. If breathing difficulties develop, move victim away from source of exposure and into fresh air in a position comfortable for breathing. Seek immediate medical attention.
- Skin Contact:** Skin Contact: Remove contaminated shoes and clothing, and flush affected area(s) with large amounts of water. If skin surface is damaged, apply a clean dressing and seek medical attention. If skin surface is not damaged, cleanse affected area(s) thoroughly by washing with mild soap and water or a waterless hand cleaner. If irritation or redness develops, seek medical attention. Wash contaminated clothing before reuse.
- Eye Contact:** Eye Contact: If irritation or redness develops from exposure, flush eyes with clean water. If symptoms persist, seek medical attention.
- Ingestion:** Ingestion: Aspiration hazard: Do not induce vomiting or give anything by mouth because this material can enter the lungs and cause severe lung damage. If victim is drowsy or unconscious and vomiting, place on the left side with the head down. If possible, do not leave victim unattended and observe closely for adequacy of breathing. Seek medical attention.

Take proper precautions to ensure your own health and safety before attempting rescue or providing first aid.

Eye Contact: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. If irritation or redness develops from exposure, flush eyes with clean water. If symptoms persist, seek medical attention.

Skin Contact: Remove contaminated shoes and clothing, and flush affected area(s) with large amounts of water. If skin surface is damaged, apply a clean dressing and seek medical attention. If skin surface is not damaged, cleanse affected area(s) thoroughly by washing with mild soap and water or a waterless hand cleaner. If irritation or redness develops, seek medical attention. Wash contaminated clothing before reuse.

Inhalation: Move to fresh air. Oxygen or artificial respiration if needed. IF exposed or concerned: Get medical advice/attention.

Ingestion: Do NOT induce vomiting. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Call a poison control center immediately.

Most important symptoms and effects, both acute and delayed: Overexposure to vapors may result in respiratory tract irritation, coughing, nausea, or headaches. Prolonged or repeated contact may dry skin and cause irritation.

Notes to Physician: Treat symptomatically

5 FIRE FIGHTING MEASURES

- Flash Point:** > 118 F
- Flash Point Method:** Seta Flash Closed Cup
- Burning Rate:** N/A
- Autoignition Temp:** N/A
- LEL:** N/A
- UEL:** N/A

Extinguishing Media: Dry chemical, carbon dioxide, or foam is recommended. Water spray is recommended to cool or protect exposed materials or structures. Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces. Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam. Water may be ineffective for extinguishment, unless used under favorable conditions by experienced fire fighters.



PB Clear Low Odor 20-PBCLO-DSF

Specific hazards arising from the chemical

Unusual Fire & Explosion Hazards: This material can be ignited by heat, sparks, flames, or other sources of ignition (e.g., static electricity, pilot lights, mechanical/electrical equipment, and electronic devices such as cell phones, computers, calculators, and pagers which have not been certified as intrinsically safe) This product will float and can be reignited on surface water. Vapors are heavier than air and can accumulate in low areas. If container is not properly cooled, it can rupture in the heat of a fire.

Hazardous Combustion Products: Combustion may yield smoke, carbon monoxide, and other products of incomplete combustion.

Special protective actions for fire-fighters: For fires beyond the initial stage, emergency responders in the immediate hazard area should wear protective clothing. When the potential chemical hazard is unknown, in enclosed or confined spaces, a self-contained breathing apparatus should be worn. In addition, wear other appropriate protective equipment as conditions warrant (see Section 8). Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Stop spill/release if it can be done safely. Move undamaged containers from immediate hazard area if it can be done safely. Water spray may be useful in minimizing or dispersing vapors and to protect personnel. Cool equipment exposed to fire with water, if it can be done safely. Avoid spreading burning liquid with water used for cooling purpose

6

ACCIDENTAL RELEASE MEASURES

Take proper precautions to ensure your own health and safety before attempting spill control or clean-up.

Personal precautions, protective equipment and emergency procedures: Spillages of liquid product will create a fire hazard. Keep all sources of ignition and hot metal surfaces away from spill/release if safe to do so. Stay upwind and away from spill/release. Avoid direct contact with material. For large spillages, notify persons down wind of the spill/release, isolate immediate hazard area and keep unauthorized personnel out. Wear appropriate protective equipment, including respiratory protection, as conditions warrant. Material can create slippery conditions.

Environmental Precautions: Stop and contain spill/release if it can be done safely. Prevent spilled material from entering sewers, storm drains, other unauthorized drainage systems, and natural waterways. Use foam on spills to minimize vapors. Use water sparingly to minimize environmental contamination and reduce disposal requirements. If spill occurs on water notify appropriate authorities and advise shipping of any hazard. Spills into or upon navigable waters, the contiguous zone, or adjoining shorelines that cause a sheen or discoloration on the surface of the water, may require notification of the National Response Center (phone number 800-424-8802).

Methods and material for containment and cleaning up: Notify relevant authorities in accordance with all applicable regulations. Immediate cleanup of any spill is recommended. Dike far ahead of spill for later recovery or disposal. Absorb spill with inert material such as sand or vermiculite, and place in suitable container for disposal. If spilled on water remove with appropriate methods (e.g. skimming, booms or absorbents). In case of soil contamination, remove contaminated soil for remediation or disposal, in accordance with local regulations. Recommended measures are based on the most likely spillage scenarios for this material; however local conditions and regulations may influence or limit the choice of appropriate actions to be taken.

7

HANDLING AND STORAGE

Handling Precautions:

Precautions for safe handling: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ensure adequate ventilation. Do not use pressure to empty drums. Keep away from open flames, hot surfaces and sources of ignition. Material can create slippery conditions.

Storage Requirements:

Conditions for safe storage: Keep container(s) tightly closed and properly labeled. Use and store this material in cool, dry, well-ventilated areas away from heat, direct sunlight, hot metal surfaces, and all sources of ignition. Store only in approved containers. Keep away from any incompatible material (see Section 10). Protect container(s) against physical damage. Indoor storage should meet OSHA standards and appropriate fire codes. "Empty" containers retain residue and may be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may cause injury or death. "Empty" drums should be completely drained, properly bunged, and promptly shipped to the supplier or a drum reconditioner. All containers should be disposed of in an



PB Clear Low Odor 20-PBCLO-DSF

environmentally safe manner and in accordance with governmental regulations. Before working on or in tanks which contain or have contained this material, refer to OSHA regulations, ANSI Z49.1, and other references pertaining to cleaning, repairing, welding, or other contemplated operations.

Storage:

Store and transport in accordance with all applicable laws. Keep containers tightly closed and store in a cool, dry, well-ventilated place, plainly labeled, and out of closed vehicles. Keep away from all ignition sources. Containers should be able to withstand pressures expected from warming and cooling in storage. All electrical equipment in areas where this material is stored or handled should be installed in accordance with applicable regulatory requirements and the National Electrical Code.

8

EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls:

Note: State, local or other agencies or advisory groups may have established more stringent limits. Consult an industrial hygienist or similar professional, or your local agencies, for further information.

Engineering controls: The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Control measures to consider: Adequate ventilation should be provided so that exposure limits are not exceeded. Use explosion-proof ventilation equipment.

Personal Protective Equipment:

Personal Protection

Personal protective equipment selections vary based on potential exposure conditions such as applications, handling practices, concentration and ventilation. Information on the selection of protective equipment for use with this material, as provided below, is based upon intended, normal usage.

Respiratory Protection: If engineering controls do not maintain airborne contaminant concentrations at a level which is adequate to protect worker health, an approved respirator may be appropriate. Respirator selection, use, and maintenance must be in accordance with regulatory requirements, if applicable. Types of respirators to be considered for this material include: Half-face filter respirator. For high airborne concentrations, use an approved supplied-air respirator, operated in positive pressure mode. Supplied air respirators with an escape bottle may be appropriate when oxygen levels are inadequate, gas/vapor warning properties are poor, or if air purifying filter capacity/rating may be exceeded.

Hand Protection: Any specific glove information provided is based on published literature and glove manufacturer data. Glove suitability and breakthrough time will differ depending on the specific use conditions. Contact the glove manufacturer for specific advice on glove selection and breakthrough times for your use conditions. Inspect and replace worn or damaged gloves. The types of gloves to be considered for this material include: If prolonged or repeated contact is likely, chemical resistant gloves are recommended. If contact with forearms is likely, wear gauntlet style gloves.

Eye Protection: If contact is likely, safety glasses with side shields are recommended.

Skin and Body Protection: Any specific clothing information provided is based on published literature or manufacturer data. The types of clothing to be considered for this material include: If prolonged or repeated contact is likely, chemical, and oil resistant clothing is recommended. Specific Hygiene Measures: Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Environmental Controls: Comply with applicable environmental regulations limiting discharge to air, water and soil. Protect the environment by applying appropriate control measures to prevent or limit emissions.

Distillates (petroleum), hydrotreated light 64742-47-8

ACGIH TLV (United States, 3/2017). Absorbed through skin. TWA: 200 mg/m³, (as total hydrocarbon vapor) 8 hours.

C9-C11 Isoalkanes 68551-16-6

MFG. TWA 1,200 mg/m³

Hydrotreated Light Naphthenic Base Oil 64742-53-6

No additional information available

NAPHTHALENESULFONIC ACID, DINONYL-, CALCIUM SALT 57855-77-3

No additional information available

PB Clear Low Odor 20-PCLO-DSF

9**PHYSICAL AND CHEMICAL PROPERTIES**

Appearance:	Clear to slightly hazy- amber
Physical State:	Liquid
Odor:	light petroleum
Odor Threshold:	N/A
Molecular Formula:	N/A
Particle Size:	N/A
Solubility:	Insoluble in water
Spec Grav./Density:	0.80
Softening Point:	N/A
Viscosity:	N/A
Percent Volatile:	N/A
Saturated Vapor Concentration:	N/A
Boiling Point:	350 °F Initial
Freezing/Melting Pt.:	N/A
Flammability:	N/A
Flash Point:	143 °F minimum.
Partition Coefficient:	N/A
Octanol:	N/A
Vapor Pressure:	N/A
Vapor Density:	HEAVIER THAN AIR
pH:	N/A
Evap. Rate:	(>1 (n-BUTYL ACETATE = 1)
Molecular weight:	N/A
Auto-Ignition Temp:	N/A
Decomp Temp:	N/A
UFL / LFL:	N/A

10**STABILITY AND REACTIVITY**

Reactivity:	Minimal hazard
Chemical Stability:	Stable
Conditions to Avoid:	Heat, spark, and open flame
Materials to Avoid:	Strong Oxidizing Agents
Hazardous Decomposition:	Combustion will produce Carbon Monoxide, Carbon Dioxide and nitrogen-oxygen compounds.
Hazardous Polymerization:	Will not occur

11**TOXICOLOGICAL INFORMATION****Distillates (petroleum), hydrotreated light 64742-47-8**

LD50 Dermal Rabbit >2000 mg/kg

LD50 Oral Rat >5000 mg/kg

Irritation/Corrosion Not available.**Sensitization** Not available**Mutagenicity** Not available**Carcinogenicity** Not available.**Teratogenicity** Not available.**Reproductive toxicity** Not available.**Specific target organ toxicity (single exposure)**Not available. **Specific target organ toxicity (repeated exposure)** Not available. **Aspiration hazard**

ASPIRATION HAZARD - Category 1

Inhalation: No known significant effects or critical hazards.**Ingestion :** May be fatal if swallowed and enters airways.**Skin contact :** Defatting to the skin. May cause skin dryness and irritation.**Eye contact :** No known significant effects or critical hazards. Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis.**C9-C11 Isoalkanes 68551-16-6**

Inhalation: LC50: > 4.9 mg/l Exposure time: 4 h Species: Rat Sex: male and female Test atmosphere: vapor Method: OECD

PB Clear Low Odor 20-PCLO-DSF

Test Guideline 403 An LC50/inhalation/4h/rat could not be determined because no mortality of rats was observed at the maximum achievable concentration. Information given is based on data obtained from similar substances.

Oral: LD50: > 5,000 mg/kg Species: Rat Sex: male and female Method: OECD Test Guideline 401 Information given is based on data obtained from similar substances.

Dermal: LD50: > 5,000 mg/kg Species: Rabbit Sex: male and female Method: OECD Test Guideline 402 Information given is based on data obtained from similar substances.

Skin irritation: May cause skin irritation and/or dermatitis. **Eye irritation:** No eye irritation. Vapors may cause irritation to the eyes, respiratory system and the skin. **Sensitization**

Not a skin sensitizer. Information given is based on data obtained from similar substances **Repeated dose toxicity** Species: Rat, male and female Sex: male and female Application Route: Inhalation

Dose: 0, 2600, 5200, 10400 mg/3 Exposure time: 13 wk

Developmental Toxicity Species: Rat Application Route: Inhalation Dose: 0, 291, 817 ppm Number of exposures: 6 h/d Test period: GD 6-15 NOAEL Teratogenicity: > 817 ppm NOAEL Maternal: > 817 ppm

Aspiration toxicity: May be fatal if swallowed and enters airways. Substances known to cause human aspiration toxicity hazards or to be regarded as if they cause human aspiration toxicity hazard.

Hydrotreated Light Naphthenic Base Oil 64742-53-6

LD50 oral rat > 5000 mg/kg

LD50 dermal rabbit > 2000 mg/kg

LC50 Inhalation - Rat 2.18 mg/l

ATE US (vapours) 2.18 mg/l/4h

ATE US (dust,mist) 2.18 mg/l/4h

Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Not classified

Respiratory or skin sensitisation : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

STOT-single exposure : Not classified

STOT-repeated exposure : Not classified

Aspiration hazard : May be fatal if swallowed and enters airways.

NAPHTHALENESULFONIC ACID, DINONYL-, CALCIUM SALT 57855-77-3

Information on likely routes of exposure

Inhalation No adverse effects due to inhalation are expected.

Skin contact Causes skin irritation.

Eye contact Causes serious eye damage.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Skin irritation. May cause redness and pain.

Acute Dermal LD50 > 10000 mg/kg

Inhalation LC50 Rat > 9 mg/l, 1 hours (no mortality) Vapor

Oral LD50 Rat > 2500 mg/kg

Oral Subacute NOAEL Rat 95 mg/kg OECD 422

Oral Subchronic NOAEL Rat 100 mg/kg, 90 days OECD 408

Skin corrosion/irritation Causes skin irritation

Serious eye damage/eye irritation Causes serious eye damage

Respiratory sensitization Based on available data, the classification criteria are not met.

Skin sensitization Based on available data, the classification criteria are not met.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Due to partial or complete lack of data the classification is not possible.

Reproductive toxicity Based on available data, the classification criteria are not met.

Specific target organ toxicity - single exposure Based on available data, the classification criteria are not met.

Specific target organ toxicity - repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

12 ECOLOGICAL INFORMATION

Distillates (petroleum), hydrotreated light 64742-47-8:

Acute EC50 >1000 mg/l Algae 72 hours

Acute LC50 >1000 mg/l Fresh water Daphnia 48 hours

Persistence and degradability: 69 % - Readily - 28 days

Bioaccumulative potential: Not available.

Mobility in soil: Not available.

C9-C11 Isoalkanes 68551-16-6

Toxicity to daphnia and other aquatic invertebrates

Toxicity to algae

C9-C11 Isoalkanes:ErL50: > 1,000 mg/l Exposure time: 72 h Species: Pseudokirchneriella subcapitata (algae) static test

Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity)

Elimination information (persistence)

Biodegradability: Expected to be biodegradable

Hydrotreated Light Naphthenic Base Oil 64742-53-6

LC50 - Fish [1] > 5000 mg/l Source: IUCLID EC50 - Crustacea [1] > 1000 mg/l Source: IUCLID EC50 96h - Algae [1] > 1000 mg/l Source: IUCLID

NAPHTHALENESULFONIC ACID, DINONYL-, CALCIUM SALT 57855-77-3

Aquatic Acute Algae NOEC Algae No effect observed up to the solubility limit in a test performed on a structural analog
Crustacea EC50 Daphnia No effect observed up to the solubility limit in a test performed on a structural analog
NOEL Daphnia 10 mg/l, 21 days , OECD 211, NOEL for mortality 4.6 mg/l, 21 days , OECD 211, NOEL for reproduction 2.2 mg/l, 21 days , OECD 211, NOEL for growth
Fish LC50 Fish No effect observed up to the solubility limit in a test performed on a structural analog

13 DISPOSAL CONSIDERATIONS

Dispose of spilled material in accordance with state and local regulations for waste that is non-hazardous by Federal definition. Note that this information applies to the material as manufactured; processing, use, or contamination may make this information inappropriate, inaccurate, or incomplete. Note that this handling and disposal information may also apply to empty containers, liners and rinsate. State or local regulations or restrictions are complex and may differ from federal regulations. This information is intended as an aid to proper handling and disposal; the final responsibility for handling and disposal is with the owner of the waste.

14 TRANSPORT INFORMATION

	UN Number	Proper Shipping Name	Hazard Class	Packaging Group
DOT/49 CFR Ground		Limited Quantity		
DOT Air	UN1950	Aerosols, Flammable, Limited Quantity	2.1	None
IMDG	UN1950	Aerosols, Limited Quantity	2.1	None
IATA	UN1950	Aerosols, Flammable, Limited Quantity	2.1	None

[%] RQ (CAS#) Substance - Reg Codes

Commercial status of components according to the United States Environmental Protection Agency's Toxic Substances Control Act (TSCA): all components are listed

Distillates, petroleum, hydrotreated light (64742-47-8)

This product is not known to contain California Prop 65 substances ≥ 1 ppm

U.S. Federal regulations: TSCA 8(a) All components are listed or exempted

Clean Air Act Section 112

(b) Hazardous Air Pollutants (HAPs) : Not listed

Clean Air Act Section 602 Class I Substances: Not listed

Clean Air Act Section 602 Class II Substances: Not listed

DEA List I Chemicals (Precursor Chemicals): Not listed

SARA 302/304 Not applicable

SARA 304 RQ : Not applicable.

SARA 311/312 Classification : ASPIRATION HAZARD - Category 1

C9-C11 Isoalkanes 68551-16-6

SARA 311/312 Hazards: Flammable (gases, aerosols, liquids, or solids) Specific target organ toxicity (single or repeated exposure)

Aspiration hazard

CERCLA Reportable Quantity: This material does not contain any components with a CERCLA RQ.

SARA 302 Reportable Quantity: This material does not contain any components with a SARA 302 RQ.

SARA 302 Threshold Planning Quantity: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 304 Reportable Quantity: This material does not contain any components with a section 304 EHS RQ.

SARA 313 Ingredients: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489).

California Prop. 65 Ingredients: This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

Hydrotreated Light Naphthenic Base Oil 64742-53-6

This product or mixture is not known to contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

This product does not contain chemicals known to the State of California to cause cancer, birth defects, or other reproductive harm.

Regulatory Code Legend

NFPA:HM Health = 1, Fire = 2, Reactivity = 0, Specific Hazard = None

IS III: Health = 1, Fire = 2, Physical Hazard = 0



HMIS	
HEALTH	<input type="checkbox"/> 1
FLAMMABILITY	<input type="checkbox"/> 2
PHYSICAL HAZARD	<input type="checkbox"/> 0
PERSONAL PROTECTION	<input type="checkbox"/>

Note:

For industrial use only. The information contained herein is accurate to the best of our knowledge. We do not suggest or guarantee that any hazards listed herein are the only ones which exist. B l a s t e r makes no warranty of any kind, express or implied, concerning the safe use of this material in your process or in combination with other substances. Effects can be aggravated by other materials and/or this material may aggravate or add to the effects of other materials. This material may be released from gas, liquid, or solid materials made directly or indirectly from it. User has the sole responsibility to determine the suitability of the materials for any use and the manner of use contemplated. User must meet all applicable safety and health standards. Possession of an SDS does not indicate that the possessor of the SDS was a purchaser or user of the subject product.

Revision Date: 7/3/2025

Print Date: 07/07/2025